

**2A20-2****HAZARDOUS LOCATION HEATING THERMOSTAT**

For use in Hazardous Atmospheres (Oil Refineries, Grain Elevators, Munitions Plants, Flour Plants, Hospital Operating Rooms)

FEATURES

- Evenly calibrated dial and adjustment knob to simplify setting.
- High electrical rating allows operation of most equipment without use of relays or motor starter.
- Hydraulic action element — unaffected by motion — no leveling required.
- 1/2" female pipe connection for wiring.

SPECIFICATIONS

Dimensions 6 1/8" H x 5 3/8" W x 4" D + 5/8" Knob
(Add 2 7/8" for height of coil)

Agency U.L. listed Div. 1 (Class I Group D; Class II Groups E, F, & G) and C.S.A. certified

Model Number	Range	Differential	Switch Action	Full Electrical Rating	Bulb Size	Capillary Length	Motor Rating (Full Load)		Resistive (Non-Inductive)	
							120 VAC	240 VAC	120 VAC	240 VAC
2A20-2 ①	40 to 90°F (4 to 32°C)	Fixed 3°F (1.6°C)	Open on Rise	FG See page 416	—	—	14.0A	7.0A	25.0A	20.0A

① 2A20-2 has external knob to adjust setting without removing cover.

**201-8****HEAVY DUTY SPACE THERMOSTATS
FOR HEATING AND COOLING**

Designed for use in Garages, Factories, Warehouses and Similar Commercial and Industrial Installations

FEATURES

- Dust, moisture and vermin resistant heavy metal case.
- No leveling required — Mounts in any position.
- Quick response to temperature changes.
- Nickel plated element.
- Extra rugged switch mechanism.

SPECIFICATIONS

Dimensions 5 3/8" H + 2 1/2" coil x 2 5/16" W x 2 9/16" D

Finish Grey color

Agency U.L. listed and C.S.A. approved

Model Number	Range	Differential	Switch Action	Full Electrical Rating	Motor Rating (Full Load)		Valves and Relays		Resistive	
					120 VAC	240 VAC	120 VAC	240 VAC	120 VAC	240 VAC
201-8	20 to 90°F (-7 to +32°C)	Adj. 3 to 20°F (2 to 11°C)	Close on Rise	FGH See page 416	16.0A	8.0A	5.6A	2.8A	25.0A	22.0A